

32 or 36-Gallon Recycle Receptacle with Metal Recessed Top



This is a heavy duty recycled plastic recycle receptacle ready for many years of trouble-free and maintenance-free service. We start with a welded steel frame painted with our zinc advantage paint system, then using all stainless-steel fasteners attach nineteen 5/4" x 4" recycled plastic slats that have a limited 15-year warranty. Then we add our heavy duty 32 or 36-gallon rotary molded liner and a heavy duty steel flat top and anchor kit, for a truly green receptacle that will last for years! With our fourteen colors of slats six colors of tops, you can create many color combinations to match your decor.

- ***Each receptacle contains 646 milk jugs saved from the land fill!***
- Many color options to choose from. **See page 2 for Slat & Top Color Options available.**
- Great design to match your school or company colors or inserted sign panel. (Minimum quantities may apply for some custom colors*)
- Dimensions: 36-Gallon: Top 28" O.D. x Height 33 3/4" 32-Gallon: Top 28" OD x Height
- Heavy duty 1/8" Nominal Thickness rotary molded liner included.
- Our durable Super TGIC powder coat paint Zinc Advantage system. Paint options details on page 2.
- Anchor kit and Stainless Steel coated Top security cable included.
- Weight: 125 pounds
- Heavy Duty 16 Gauge Galvanneal top w/Super TGIC Powder coat. Design is optimized to reduce rain collection by 66% or heavy 18 Gauge Galvanneal Rain Guard or Ash Urn with Super TGIC Powder Coat with the design optimized to eliminate most of the rain collection.

Side Mounted Ash Urn Option:

- No Ash Urn
- Side Mounted Ash Urn



Receptacle Mounting Options:


- Surface Mount (Standard)
- Surface Pedestal Mount
- Inground Pedestal Mount

See Web for Options Pricing!

Top Options:

1. Steel Top (Standard)
2. Steel Top, LG Rain Guard
3. Steel Top, LG Ash Urn
4. Steel Top, LG Rain Guard, Removable Ash Urn
5. Steel Top, LG Rain Guard, Covered Ash Urn

Available 18-Gauge Laser Cut Recycle Plaques



OCCOutdoors, Inc. Warranty: 20 Years Structural, 15 years on Recycled Plastic Slats and One year paint when installed and maintained properly. We agree to repair or replace, any items determined to be defective. Items specifically not covered by this warranty include vandalism, man-made or natural disasters, lack of maintenance, normal weathering or wear and tear due to public abuse.

NOTES:

1. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS.
2. ALL DIMENSIONS ARE CONSIDERED TRUE AND REFLECT MANUFACTURER'S SPECIFICATIONS
3. DO NOT SCALE DRAWING.

This document contains OCC Outdoors Proprietary Information. No intellectual copyright or license is granted by OCC Outdoors in connection with it. It is delivered on the express condition that the document and the information contained in it shall be treated as confidential, shall not be used for and purpose other than that for which it is hereby delivered (the use and maintenance of the product supplied). It shall not be disclosed in whole or part to third parties and shall not be duplicated in any manner without OCC Outdoors's prior approval.

OCC Outdoors Products

PH: 1-800-821-7670
EMAIL - occcontact@occoutdoors.com Fax:
1-317-862-9422

Part #: GB-RECY-32/36-SUN-MT

Date: 5/10/17

Page 1 of 2

Green Brook 32 or 36-Gallon Recycling Receptacle with Metal Recessed Top

v 1.1

A

B

C

D

Zinc Advantage Process Details:

Zinc rich primer & Super TGIC powder coat Finishing operations.







Advantages:

1. Sand blasts each unit down to shiny metal.
2. Clean and hand inspects each unit.
3. Powder coat with 70 % zinc rich epoxy resin primer.
4. Partially bake the primer.
5. Powder coat with SUPER TGIC Polyester finish coat.
6. Final bake, creating a molecular bond between the steel, primer and finish coat.
7. Each part is tested by a Xylene test to insure a complete cure.

1. A very tough durable finish with 5 times the fade resistance of standard TGIC powder coatings with a 3H pencil hardness. (All test conducted in South Florida.)
2. If scratched through to the metal, the zinc rich primer greatly reduce rust and the potential for the migration of rust.
3. This system is cured and each unit test for cure so many types of paint used for graffiti can be clean with mild solvents.

Our paint manufacturer's Zinc rich primer TGIC Polyester out lasts all major competitors on the 4000 hour salt spray test per ASTM B117. Detailed reports available by request.

Steel Top Colors Available;

Black, RAL 9005	
Bronze, C33	
Green, RAL 6005	
Blue, RAL 5012	
Silver Gray, 70049	
Burgundy, RAL 3007	

Slat Colors Available:

Color Matching Information: OCCOutdoors makes every effort to present colors as accurately as possible. The colors have been produced electronically and are provided for general color information and illustration purposes only. Because of the differences in computer monitors, printers, other hardware and software combinations, the depicted results are intended to be used as approximations of color and not as definitive representations and should not be relied upon or used as such. We cannot guarantee you will achieve desired results without verifying an actual color sample of your actual color selection. For specific advice regarding your project, we recommend that you contact OCC Outdoors: Phone: 1-800-821-7670 email: occontact@occoutdoors.com

Page 2 of ?2 OCC Outdoors Products PH: 1-800-821-7670 EMAIL -
 occontact@occoutdoors.com
 Fax: 1-317-862-9422
 Part #: GB-RECY-32-36-SUN-MT

8

7

6

5

4

3

2

1

8

7

6

5

4

3

2

1

A

B

C

D