

Pole Mounted Open Bag Trash Receptacle

Pole mounted open bag trash receptacle is a low cost option for trash collection and has several advantages. Great for city streets, parks, trails or special events.

How they work

After the receptacle is mounted, any size of plastic bag can be loaded by inserting the top of the bag up through the ring and opening the bag and pulled down over the outside of the bag hanger ring. The elastic strap is then pulled down around the ring and into the groove around the hanger ring retaining the bag.

To empty or change the trash bag pull the elastic band from around the bag hanger ring and the trash bag falls free.

Advantages

- They are low cost so you can place them more frequently for better trash collection.
- The collection personnel can see when they need to be emptied.
- Easy to empty and change bags, no lifting the bag up and out of a receptacle.
- Utilizes many bag sizes from 10 gallons up to 55 gallons.
- Different colors of trash bags can be used to color code for trash, or recycling.
- They can be mounted to nearly any size of type of pole.
- They can easily be moved.
- Available in Green, Black or Bronze, Silver Gray, Burgundy and Blue. Custom colors available upon request.
- All finishes are weather and UV resistant super TGIC powder coat finishes. **See page 2 for Colors and Super TGIC Powder Coat Finish Details.**



OCCOutdoors, Inc. Warranty: 20 Years Structural and one year paint when installed and maintained properly. We agree to repair or replace, any items determined to be defective. Items specifically not covered by this warranty include vandalism, man-made or natural disasters, lack of maintenance, normal weathering or wear and tear due to public abuse.

NOTES:

1. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS.
2. ALL DIMENSIONS ARE CONSIDERED TRUE AND REFLECT MANUFACTURER'S SPECIFICATIONS
3. DO NOT SCALE DRAWING.

This document contains OCC Outdoors Proprietary Information. No intellectual copyright or license is granted by OCC Outdoors in connection with it. It is delivered on the express condition that the document and the information contained in it shall be treated as confidential, shall not be used for and purpose other than that for which it is hereby delivered (the use and maintenance of the product supplied). It shall not be disclosed in whole or part to third parties and shall not be duplicated in any manner without OCC Outdoors's prior approval.

OCC Outdoors Products

PH: 1-800-821-7670

EMAIL - occontact@occoutdoors.com

Fax: 1-317-862-9422

20-Gallon Pole Mountable Trash Receptacle

Part #: REC-POLMT-OBS

Date: 11/30/16

Page 1 of 2

v 1.0

OCC Colors and Paint Details

Bench Colors: OCC offers hundreds of color including the standard RAL colors, Architectural series and custom mixed colors. Please contact us with you color requirements. For more details please go to:
www.occoutdoors.com/blog/understanding-nonstandard-colors-cost.

OCC Standard Colors

Black (RAL 9005)	Bronze (C33)
Green (RAL 6005)	Blue (RAL 5012)
Silver Gray (70049)	Burgundy (RAL 3004)

Zinc Advantage Process Details:

Zinc rich primer & Super TGIC powder coat Finishing operations.

1. Sand blasts each unit down to shiny metal.
2. Clean and hand inspects each unit.
3. Powder coat with 70 % zinc rich epoxy resin primer.
4. Partially bake the primer.
5. Powder coat with SUPER TGIC Polyester finish coat.
6. Final bake, creating a molecular bond between the steel, primer and finish coat.
7. Each part is tested by a Xylene test to insure a complete cure.

Advantages:

1. A very tough durable finish with 5 times the fade resistance of standard TGIC powder coatings with a 3H pencil hardness. (All test conducted in South Florida.)
2. If scratched through to the metal, the zinc rich primer greatly reduce rust and the potential for the migration of rust.
3. This system is cured and each unit test for cure so many types of paint used for graffiti can be clean with mild solvents.

Our paint manufacturer's Zinc Rich Primer TGIC Polyester out lasts all major competitors on the 4000 hour salt spray test per ASTM B117. Detailed reports available by request.