


## 50-Gallon Heavy Duty Trash Receptacle with Flat Steel Top

- •Heavy Duty 16 Gauge galvanneal top with durable Super TGIC Powder Coat Zinc Advantage System
- •Heavy Duty 1/8" nominal thickness rotary molded liner
- Anchor Kit Included
- •Coated Stainless Steel Security Cable Included
- •Top Optimized design to help catch more trash and reduce rain collection by 66%
- •Heavy 18 gauge galvanneal rain guard or ash urn with super TGIC powder coat, with an optimized design to eliminate most of the remaining rain collection.
- •1/4" x 2" Steel Vertical slats & elevating inner bottom ring with leveling feet
- •Weight: 136 Lbs.

Optional Heavy Duty Laser Cut Stainless Steel Recycle Plaques





#### **Top Options:**

- (1) Steel Top (2) Steel Top. LG Rain Guard
- (3) Steel Top, LG Ash Urn
- (4) Steel Top. LG Rain Guard, Removable Ash Urn
- (5) Steel Top. LG Rain Guard, Covered Ash Urn
- (6) Plastic Dome Top, Door
- (7) Plastic Dual Opening Dome Top











**Other Options:** 

• Surface Mount (Standard)

Surface Pedestal Mount

• Side Mounted Ash Urn

In-ground Pedestal Mount



### **Available Receptacle Colors:**

- Bronze: C33 Green: RAL 6005
- Blue: RAL 5012
- Black: RAL 9005 Silver Gray: 70049
  - Burgundy: RAL 3004
  - Custom colors on request

#### Dome top colors:

○ Light Granite (+\$12.00) ○ Dark Granite (+\$12.00) ○ Beige Granite (+\$12.00)











OCCOutdoors, Inc. Warranty: 20 Years Structural and one year paint when installed and maintained properly. We agree to repair or replace, any items determined to be defective. Items specifically not covered by this warranty include vandalism, man-made or natural disasters, lack of maintenance, normal weathering or wear and tear due to public abuse.

- INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS. ALL DIMENSIONS APE CONSIDERED TRUE AND PETLECT MANUFACTURER'S SPECIFICATIONS
- 3. DO NOI SCALE DRAWING.

.25 H.R. Flatbar

2-Feet 2 x 25 x 19 125

This document contains OCC Outdoors Proprietary Information. No intellectual copyright or license is granted by OCC Outdoors in connection with it. It is delivered on the express condition that the document and the information contained in it shall be treated as confidential, shall not be used for and purpose other than that for which it is hereby delivered (the use and maintenance of the product supplied). It shall not be disclosed in whole or part to third parties and shall not be duplicated in any manner without OCC Outdoors's prior approval.

#### **OCC Outdoors Products**

PH: 1-800-821-7670

EMAIL - occcontact@occoutdoors.com

Fax: 1-317-862-9422

Part #: REC-SL-50-FT

### **50-Gallon Heavy Duty** Trash Receptacle With **Heavy Duty Liner and** Flat Steel Top

v1.1 Date: 3/12/18

# Our Durable Super TGIC Powder Coat Paint Zinc Advantage System

# **Zinc Advantage Process Details:**

Zinc Rich Primer & Super TGIC Powder Coat Finishing Operations.

- 1. Sand blasts each unit down to shiny metal.
- 2. Clean and hand inspects each unit.
- 3. Powder coat with 70 % zinc rich epoxy resin primer.
- 4. Partially bake the primmer.
- 5. Powder coat with SUPER TGIC Polyester finish coat.
- 6. Final bake, creating a molecular bond between the steel, primer and finish coat.
- 7. Each part is tested by a Xylene test to insure a complete cure.

# **Advantages:**

- 1. A very tough durable finish with 5 times the fade resistance of standard TGIC powder coatings with a 3H pencil hardness. (All test conducted in South Florida.)
- 2. If scratched through to the metal, the zinc rich primer greatly reduce rust and the potential for the migration of rust.
- 3. This system is cured and each unit test for cure so many types of paint used for graffiti can be clean with mild solvents.

Our paint manufacturer's Zinc rich primer TGIC Polyester out lasts all major competitors on the 4000 hour salt spray test per ASTM B117. Detailed reports available by request.

Page 2 of 2 OCC Outdoors Products PH: 1-800-821-7670 EMAIL - occcontact@occoutdoors.com Fax: 1-317-862-9422 Super TGIC Powder Coat Process