



36-Gallon Single Stream Recycling Bin

Ornamental recycling bin, vertical slatted 36-gallon recycle bin with heavy Steel top and polyethylene liner, Anchor Kit and Top Retainer all included! Fully assembled, pre-drilled mounting holes in feet (Anchoring hardware included).

- Available in Black, Bronze, Green, Silver grey, Burgundy or Blue. Custom colors available upon request. See Page 2 for Color Details.
- 18-gauge Laser Cut SS Plaques available for Paper, Cans and Bottles, Plastic, Trash, Recyclables, Compost and Landfill
- All-steel heavy duty construction, 1/8" x 2" edged Galvanneal slats
- Our durable Super TGIC powder coat paint Zinc Advantage system. Paint options details on Page 2.
- Mounted on skids to assure trouble-free shipping,
- Physical dimensions 27 3/4' diameter x 36" tall
- Weight 75 pounds

Available Stainless Steel Plaques



Top Options Available:
See Web for Pricing

Flat Top & Dome Top Colors Available:

- | | |
|---|---|
| <ul style="list-style-type: none"> • Steel Top (Standard) • Steel Top w/Rain Guard • Steel Top W/Ash Urn • Dome Top w/Door • Dual Opening dome Top | <ul style="list-style-type: none"> • Black, All Tops • Brown, All Tops • Green, All Tops • Blue, All Tops • Grey Granite, Dome Tops • Black Granite:, Dome Tops • Brown Granite, Dome Tops |
|---|---|



OCCOutdoors, Inc. Warranty: 20 Years Structural and one year paint when installed and maintained properly. We agree to repair or replace, any items determined to be defective. Items specifically not covered by this warranty include vandalism, man-made or natural disasters, lack of maintenance, normal weathering or wear and tear due to public abuse.

- NOTES:
1. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS.
 2. ALL DIMENSIONS ARE CONSIDERED TRUE AND REFLECT MANUFACTURER'S SPECIFICATIONS
 3. DO NOT SCALE DRAWING.

OCC Outdoors Products

PH: 1-800-821-7670

EMAIL - occcontact@occoutdoors.com

Fax: 1-317-862-9422

36-Gallon Round

Ornamental Recycling Bin

Part #: RECY-ORN-36

Date: 2/19/2018

Page 1 of 2

v 1.2

This document contains OCC Outdoors Proprietary Information. No intellectual copyright or license is granted by OCC Outdoors in connection with it. It is delivered on the express condition that the document and the information contained in it shall be treated as confidential, shall not be used for and purpose other than that for which it is hereby delivered (the use and maintenance of the product supplied). It shall not be disclosed in whole or part to third parties and shall not be duplicated in any manner without OCC Outdoors's prior approval.

OCC Colors and Paint Details

Bench Colors: OCC offers hundreds of color including the standard RAL colors, Architectural series and custom mixed colors. Please contact us with your color requirements. For more details please go to: www.occoutdoors.com/blog/understanding-nonstandard-colors-cost.

OCC Standard Colors

Black (RAL 9005)




Green (RAL 6005)



Silver Gray (70049)



Bronze (C33)



Blue (RAL 5012)



Burgundy (RAL 3004)



Zinc Advantage Process Details:

Zinc rich primer & Super TGIC powder coat Finishing operations.

1. Sand blasts each unit down to shiny metal.
2. Clean and hand inspects each unit.
3. Powder coat with 70 % zinc rich epoxy resin primer.
4. Partially bake the primer.
5. Powder coat with SUPER TGIC Polyester finish coat.
6. Final bake, creating a molecular bond between the steel, primer and finish coat.
7. Each part is tested by a Xylene test to insure a complete cure.

Advantages:

1. A very tough durable finish with 5 times the fade resistance of standard TGIC powder coatings with a 3H pencil hardness. (All test conducted in South Florida.)
2. If scratched through to the metal, the zinc rich primer greatly reduce rust and the potential for the migration of rust.
3. This system is cured and each unit test for cure so many types of paint used for graffiti can be clean with mild solvents.

Our paint manufacturer's Zinc Rich Primer TGIC Polyester out lasts all major competitors on the 4000 hour salt spray test per ASTM B117. Detailed reports available by request.