

g a e e o e e e a e P o e  
 oo a a g a e e o e e e a e a oo g e a a e o  
 a a . a e e o e a o 0 e a a a g e l  
 a e e e e a e a o o e o e f o a e a g a e e .  
 o o 7 g a e e 9 e a a . e o e a o  
 a e e e e a o e e e o v g e a a v e g . e  
 o e P o e e g o 12 o a e a a e o e v e o .

**Zinc Advantage Process Details:**

Zinc rich primer & Super TGIC powder coat Finishing operations.

1. Sand blasts each unit down to shiny metal.
2. Clean and hand inspects each unit.
3. Powder coat with 70 % zinc rich epoxy resin primer.
4. Partially bake the primmer.
5. Powder coat with SUPER TGIC Polyester finish coat.
6. Final bake, creating a molecular bond between the steel, primer and finish coat.
7. Each part is tested by a Xylene test to insure a complete cure.

**Advantages:**

1. A very tough durable finish with 5 times the fade resistance of standard TGIC powder coatings with a 3H pencil hardness. (All test conducted in South Florida.)
2. If scratched through to the metal, the zinc rich primer greatly reduce rust and the potential for the migration of rust.
3. This system is cured and each unit test for cure so many types of paint used for graffiti can be clean with mild solvents.

**Our paint manufacturer's Zinc rich primer TGIC Polyester out lasts all major competitors on the 4000 hour salt spray test per ASTM B117. Detailed reports available by request.**

OCC offers hundreds of color including the standard RAL colors, Architectural series and custom mixed colors. Please contact us with you color requirements. For more details please go to:  
[www.occoutdoors.com/blog/understanding-nonstandard-colors-cost](http://www.occoutdoors.com/blog/understanding-nonstandard-colors-cost).



OCCOutdoors, Inc. Warranty: 20 Years Structural and one year paint when installed and maintained properly. We agree to repair or replace, any items determined to be defective. Items specifically not covered by this warranty include vandalism, man-made or natural disasters, lack of maintenance, normal weathering or wear and tear due to public abuse.

NOTES:  
 1. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS.  
 2. ALL DIMENSIONS ARE CONSIDERED TRUE AND REFLECT MANUFACTURER'S SPECIFICATIONS  
 3. DO NOT SCALE DRAWING.

This document contains OCC Outdoors Proprietary Information. No intellectual copyright or license is granted by OCC Outdoors in connection with it. It is delivered on the express condition that the document and the information contained in it shall be treated as confidential, shall not be used for and purpose other than that for which it is hereby delivered (the use and maintenance of the product supplied). It shall not be disclosed in whole or part to third parties and shall not be duplicated in any manner without OCC Outdoors's prior approval.

**OCC Outdoors Products**  
 PH: 1-800-821-7670  
 EMAIL - [occcontact@occoutdoors.com](mailto:occcontact@occoutdoors.com)  
 Fax: 1-317-862-9422

**Part #: SMR-40**

Date: 2/9/17 Page 1 of 1 v; 1.0

g a e e o e  
 e e a e P o e